



## THE IDEAL DISPENSER

The TS dispenser is reliable, accurate, easy to operate & maintain. It comes with different types of pumps depending on the type of liquid, speed & volumes.

The TS model comes with “MastriqOne” integrated tinting software that ensures a very high level of performance and control during the tinting process.

“MastriqOne” is easy to use, built on the latest platform, allow paint companies to have better access & control over their retail shops. Clients can have uninterrupted access to data, they can integrate & analyse quickly to improve performance.

New upgrades, databases can be updated at the click of a mouse.

The New “MastriqOne” software is designed to Enhance the instore tinting experience.



## TECHNICAL SPECIFICATIONS

DISPENSING TYPE	Sequential / Simultaneous
DISPENSING MODE	Volumetric
MINIMUM DISPENSING	1/384 fl. oz. (0.077 ml) using 4 mm nozzles 1/1000 fl. oz. (0.33 ml) using 2 mm nozzles
DISPENSING SPEED	0.26 Ltr /min
NUMBER OF CANISTERS	Up to 16
CANISTER CAPACITY	2 Ltr.
COLORANT STIRRING	Automatic and programmable
CAN SENSOR	Standard
CAN HANDLING	Manually adjustable can shelf
HUMIDIFIER CAP	Automatic
LASER TARGET LIGHT	Optional
COMPATIBILITY	Universal / Water / Solvent colorant system
POWER SUPPLY	220V / 50Hz & 110V / 60Hz
MACHINE NET WEIGHT	143 kg
MAXIMUM MACHINE SIZE	W 566 x D 915 x H 1033 mm
SOFTWARE	“MastriqOne” Operating software

